

Package: multiCorr (via r-universe)

September 16, 2026

Type Package

Title Multicovariance and Multicorrelation for p-Variables

Version 0.1.0

Description Implements the multicorrelation coefficient for p-variables as described in Cankaya (2023). The package provides a numerically stable implementation using logarithmic transformations and a log-sum-exp approach to reduce numerical overflow and underflow when calculations involve a large number of variables.

License GPL-3

Encoding UTF-8

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Mehmet Niyazi Cankaya [aut, cre]

Maintainer Mehmet Niyazi Cankaya <mehmet.cankaya@usak.edu.tr>

Repository <https://githubmehmetcankaya.r-universe.dev>

Date/Publication 2026-09-15 11:50:08 UTC

RemoteUrl <https://github.com/cran/multiCorr>

RemoteRef HEAD

RemoteSha 951727a539e2413a39db92d741a1ad37e404da71

Contents

multicorrelation	2
Index	3

multicorrelation	<i>Calculate Multicorrelation for p-Variables</i>
------------------	---

Description

Computes the multicorrelation coefficient for p variables.

Usage

```
multicorrelation(x, r = 1)
```

Arguments

x	A numeric matrix or data frame.
r	A positive numeric power parameter. Default is 1.

Details

Each variable is centered by its arithmetic mean and scaled by its mean absolute deviation from the mean. Logarithmic transformations and a log-sum-exp approach are used to improve numerical stability.

Value

A numeric multicorrelation coefficient.

References

Cankaya, M. N. (2023). Multicovariance and Multicorrelation for p-variables. In *Mathematical Methods for Engineering Applications (ICMASE 2022)*, pp. 273-284. Cham: Springer International Publishing.

Examples

```
set.seed(123)
X <- matrix(rnorm(1000), nrow = 100, ncol = 10)
multicorrelation(X)

multicorrelation(X, r = 2)
```

Index

multicorrelation, [2](#)